

PLP-P2C155

› 15" VESA Mount / Wall Mount Standalone Touch Monitor



Features



- IP65 (front) with Aluminum bezel
- Operating temperature -20°C~60°C
- Modularized I/O: VGA + DVI-D + HDMI
- Wall mount / VESA 100 mounting

Specifications

| | |
|------------------------|--|
| Model | PLP-P2C155 |
| Customer (2nd) Display | 15" XGA LCD (450 cd/m ²) |
| Display Resolution | 1024 x 768 (XGA) |
| Dimensions (Panel) | 366 x 280 x 54 mm (W x H x D) |
| Viewing Angle | Horizontal -80°~80°, Vertical -80°~70° |
| I/O Ports | VGA DVI-I cable (support DVI-D signal only) HDMI USB (touch connection) |
| Power Supply | Type: DC12V/3.3A/40W/φ2.5 power adapter AC Input: 90~264 Vac, 47-63 Hz |

Environment

| | |
|-----------------|--------------------------|
| EMC & Safety | CE |
| Operating Temp. | -20°C~60°C (-4°F~140°F) |
| Storage Temp. | -30°C~70°C (-22°F~158°F) |
| Humidity | 5%~95% |

Application

- Automation
- Information
- Transportation
- Medical
- Banking
- Chemistry

Highlights



I/O Panel View



Dimensions

